



FIBERTECH DOOR SYSTEM

MAKE THE BEST IMPRESSION

Fibertech Tent Doors – An impressive entry to any tent, making the tent environment more inviting, functional and climate controlled for events year round.

- Simplified design, installs in minutes and always functions with a minimum of care
- These fiberglass doors are chip, dent and rust resistant and provide lasting durability
- Engineered for single or double door applications, with or without panic hardware
- Conforms to code standards for tents
- Tempered glass inserts with stainless steel hardware
- Powder coated steel frame for strength and durability
- Systems come complete with mounting hardware and installation tools
- Mounting brackets are available for most brands of tents, or we will match your needs



All doors come in shipping crates. Excellent for storage and handling.



Clear Door



Interior View With Panic Hardware



French Grid



FIBERTECH DOOR SYSTEM

Tent Door Assembly Instructions

1. Insert Pc (K) into either Header Tube and secure with Pc (B) with Washer (Finger Tight).
2. Slide opposite Side Frame Pc over Pc (K) and secure with Pc (B) with Washer (Finger Tight).
3. Drop Pc (J) over the top of header Tubes and align with Holes. Secure with Pc (A) Bolt & Washer. All Bolts may now be tightened being careful not to collapse tubes.
4. Install frame where desired being careful to maintain equal distance top and bottom between jamb sections. For Tent with no Eave Tube, Extrusion Arms can install horizontally in Header, Attach to tent frame using Extension Arms (E) and Top Brackets.
5. Install doors and attach closer arms.

NOTE: Proper operation of the doors may require shimming under the base plates to obtain a true vertical jamb alignment.

Double Door Crate Contents

Sidewall Door Opening 6'1"(w) X 6'9"(h)

FRAME PARTS:

C. Left Side "L" Shaped Leg	1
D. Right Side "L" Shaped Leg	1
E. Extension Tube.....	2
F. Door Closer with Arm.....	2
G. Left Swing Door	1
H. Right Swing Door	1
J. 6' Header	1

TOOLBOX:

— Tool Box.....	1
K. 8" White Channel	1
—Top bracket for extension tube	2
— 5/16" Nylon Nut and Washer (Closer Arm)....	2
R. 3" Carriage Bolts for Top Bracket.....	2
A. 3/8" X 2-3/4" Bolts	6
B. 3/8" X 3/4" Bolts for 8" Channel.....	2
N. 3/8" Nylock Nuts	4
— 3/8" Flat Washers for Bolts in Header	6
M. 1/4" X 1/2" Thumb Screws.....	4
— Combination Box/Ratchet Wrench	1
— Fibertech Brochure.....	1
— Door Closer Instructions	1
— Extra Hardware Bag.....	1
— Packing List.....	1

